

GB SERIES

GB Series 105° Two-way Regular Concealed Hinge for Glass Doors




Specification

Opening Angle	105°
Function	Auto Close
Plate Type	Clip On
Cup Depth	12.5 mm
Cup Diameter	35 mm
Drilling Distance	3 mm - 6 mm
Door Thickness	4 mm - 6 mm
Material	Cold Rolled Steel
Height Adjustment Range	Plate Adjustment
Overlay Adjustment Range	6 mm
Depth Adjustment Range	5 mm
Finish	Copper Nickel
Packaging	200 Units per Carton


Notable Features

- Two-way hinge technology extending the service life of the hinge.




Additional Options: 1P - Individual Hinge, Caps for Arm and Cup, Mounting Plate and Screws in Sealed Bag
2P - Pair of Hinges, Caps for Arm and Cup, Mounting Plates and Screws in Sealed Bag

Drilling For Cup



Cup Installation


Screw-on



Installation Method Code
Wood Screws S2

Overlay Table


Full Overlay



$$H = 14 + K - D$$

D \ K	3	4	5	6
H	0	17	18	19
2	15	16	17	18
4	13	14	15	16


Half Overlay



$$H = 4 + K - D$$

D \ K	3	4	5	6
H	0	7	8	9
2	5	6	7	8
4	3	4	5	6


Inset



$$H = -4 + K + A$$

A \ K	3	4	5	6
H	0	1	0	-1
2	3	2	1	0
4	5	4	3	2

Minimum Reveal Table



A \ K	14	15	16	17	18	19	20	21	22
T	3	0.3	0.5	0.7	0.9	1.2	1.5	1.8	2.2
4	0.3	0.5	0.7	0.9	1.1	1.4	1.8	2.1	2.5
5	0.2	0.4	0.6	0.9	1.1	1.4	1.7	2.0	2.4
6	0.2	0.4	0.6	0.8	1.1	1.3	1.6	2.0	2.4

K = Boring distance


T = Door thickness

A = Minimum gap (A) for door with a door edge radius

L = Gap between door and panel


Note:

The minimum parameters in the reveal tables are based on doors with straight, square edges. A rounded or beveled profile will change the minimum reveal required.



L \ K	14	15	16	17	18	19	20	21	22
T	3	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
4	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.2
5	1.0	1.0	1.0	1.0	1.0	1.3	1.5	1.8	2.0
6	1.0	1.3	1.5	1.8	2.0	2.3	2.5	2.8	3.0

Hinge Adjustment



Depth Adjustment

Move the hinge laterally to adjust door gap.

Horizontal Adjustment

Rotate the hinge arm screw to increase or decrease door overlay.

Vertical Adjustment

Adjust the mounting plate to increase or decrease the door height.

Note:

The referenced adjustment range described is the product design range. The actual design of the cabinet and the drilling method may have a certain impact on the parameters.

Plate Options: DS TS FP FS FM FN YD YS YT YP